






**SPLICE SLEEVE HOLDERS
FSH/SSH SERIES**

TECHNICAL SPECIFICATIONS

Splice Technologies' currently manufactures three holders utilizing engineered materials. Commonly called splice "chips" or "holders" these devices are designed to secure a variety of mechanical and fusion splice protection sleeves, as well as other types of fiber optic devices. Listed model numbers **FSH-HS-06 & SSH-S12** will provide adequate support for a **2.9mm** after shrink diameter, while our model number **SSH-R12** will provide support for a **5.0mm** after shrink diameter component. These holders are RoHS compliant and designed with a high-peel tape adhesive for mounting into any metal or plastic splice tray or enclosure.

MODEL NUMBER	HOLDER MATERIAL	HOLDER SPECIFICATIONS	ADHESIVE TAPE MATERIAL	TAPE SPECIFICATIONS
FSH-HS-06	 Black Low Density Polyethylene	Density = 0.924 g/cm ³ Shore D Hardness = 55 Vicat Softening Temp. = 210°F Brittleness Temp. = -90°F L X W X H 1.10" X 1.00" X 0.20"	Polyethylene Foam Tape w/ Rubber Adhesive, White in color.	Thickness = 0.03 inches Peel Adhesion = 8 lb/in width Solvent Resistance = Medium Operating Temperature -20°F to +158°F
SSH-S12	 Black, High Density Silicone Rubber	Operating Temp. = -55°F to +250°F Tensile Strength = 7.0 MPa Elongation@ Break = 320% L X W X H 2.75" X 0.50" X 0.25"	3M Double-coated polyester film w/Silicone/Acrylic Adhesive Tape, Clear	Operating Temperature -55°F to +176°F
SSH-R12	 Blue, High Density Silicone Rubber	Operating Temp. = -55°F to +250°F Tensile Strength = 7.0 MPa Elongation@ Break = 320% L X W X H 2.95" X 0.50" X 0.30"	3M Double-coated polyester film w/Silicone/Acrylic Adhesive Tape, Clear	Operating Temperature -55°F to +176°F

FOR ORDERS AND QUOTES:

Phone: 1-631-924-8108
 Fax: 1-631-924-8109
 Email: sales@splicetechnologies.com
 Website: www.splicetechnologies.com